

**E59xxx65-V02**  
**Attenuator 200W**  
**N / 4.3-10 / 7/16**  
**DC-4000**



**Attenuator DC-4000 200W**

Type	N F/M	E5930365-V02	E5930565-V02	E5930665-V02	E5931065-V02
	4.3-10 F/M	E5910365-V02	E5910565-V02	E5910665-V02	E5911065-V02
	7/16 F/M	E5950365-V02	E5950565-V02	E5950665-V02	E5951065-V02
Attenuation (dB)		3	5	6	10
Attenuation Tolerance (dB)		±0.7	±0.7	±0.7	±0.7

Type	N F/M	E5931565-V02	E5932065-V02	E5933065-V02	E5934065-V02
	4.3-10 F/M	E5911565-V02	E5912065-V02	E5913065-V02	E5914065-V02
	7/16 F/M	E5951565-V02	E5952065-V02	E5953065-V02	E5954065-V02
Attenuation (dB)		15	20	30	40
Attenuation Tolerance (dB)		±0.7	±0.7	±0.8	±0.8

**Electrical Specifications**

Frequency (MHz)	DC - 4000
PIM3 (dBc, @2x43dBm)	≤ -105
Impedance (Ω)	50
Return Loss (dB)	≥ 21
Max Input Power (W)	200

**Mechanical and Environmental Specifications**

Dimension (mm)	200 x 176 x 75 (excluding connector and bracket)
Weight (kgs)	N F/M: 2.35 (including connector and bracket)
	4.3-10 F/M: 2.35 (including connector and bracket)
	7/16 F/M: 2.4 (including connector and bracket)
Ingress Protection	IP55
Operating Temperature (°C)	-55 to +125
Operating RH (%)	≤ 95
Mounting	Wall Mount

**Packing Information**

Packing Size (mm)	270 x 230 x 120
SKU (unit/inner carton)	8pieces per inner carton/box

(D)25041660/25061660/25071660/25012660/25062660/25013660/25014660/25015660  
(D)26041660/26061660/26071660/26012660/26062660/26013660/26014660/26015660  
(D)27041660/27061660/27071660/27012660/27062660/27013660/27014660/27015660

**E59xxx65-V02**  
**Attenuator 200W**  
**N / 4.3-10 / 7/16**  
**DC-4000**

