

**E56xxx95-V02**  
**Attenuator 2W**  
**N / 4.3-10 / 7/16**  
**DC-4000**



**Attenuator DC-4000 2W**

Type	N F/M	E5630395-V02	E5630695-V02	E5631095-V02	E5631595-V02
	4.3-10 F/M	E5610395-V02	E5610695-V02	E5611095-V02	E5611595-V02
	7/16 F/M	E5650395-V02	E5650695-V02	E5651095-V02	E5651595-V02
Attenuation (dB)		3	6	10	15
Attenuation Tolerance (dB)		±0.7	±0.7	±0.7	±0.7

Type	N F/M	E5632095-V02	E5633095-V02	E5634095-V02	
	4.3-10 F/M	E5612095-V02	E5613095-V02	E5614095-V02	
	7/16 F/M	E5652095-V02	E5653095-V02	E5654095-V02	
Attenuation (dB)		20	30	40	
Attenuation Tolerance (dB)		±0.7	±0.8	±0.8	

**Electrical Specifications**

Frequency (MHz)	DC - 4000
PIM3 (dBc, @2x33dBm)	≤ -120
Impedance (Ω)	50
Return Loss (dB)	≥ 21
Max Input Power (W)	2

**Mechanical and Environmental Specifications**

Dimension (mm)	N F/M: Ø30 x 35 (excluding connector and bracket)
	4.3-10 F/M: Ø30 x 35 (excluding connector and bracket)
	7/16 version: Ø35 x 35 (excluding connector and bracket)
Weight (kgs)	N F/M: 0.22 (including connector and bracket)
	4.3-10 F/M: 0.22 (including connector and bracket)
	7/16 F/M: 0.27 (including connector and bracket)
Ingress Protection	IP55
Operating Temperature (°C)	-55 to +125
Operating RH (%)	≤ 95

**Packing Information**

Packing Size (mm)	70 x 30 x 30
SKU (unit/inner carton)	100 pieces per inner carton/box

(D)220YY660  
(D)230YY660  
(D)240YY660

**E56xxx95-V02**  
**Attenuator 2W**  
**N / 4.3-10 / 7/16**  
**DC-4000**

