

**E56xxx15-V02**  
**Attenuator 5W**  
**N / 4.3-10 / 7/16**  
**DC-4000**



**Attenuator DC-4000 5W**

Type	N F/M	E5630315-v02	E5630615-v02	E5631015-v02	E5631515-v02
	4.3-10 F/M	E5610315-v02	E5610615-v02	E5611015-v02	E5611515-v02
	7/16 F/M	E5650315-v02	E5650615-v02	E5651015-v02	E5651515-v02
Attenuation (dB)		3	6	10	15
Attenuation Tolerance (dB)		±0.7	±0.7	±0.7	±0.7

Type	N F/M	E5632015-v02	E5633015-v02	E5634015-v02	
	4.3-10 F/M	E5612015-v02	E5613015-v02	E5614015-v02	
	7/16 F/M	E5652015-v02	E5653015-v02	E5654015-v02	
Attenuation (dB)		20	30	40	
Attenuation Tolerance (dB)		±0.7	±0.8	±0.8	

**Electrical Specifications**

Frequency (MHz)	DC - 4000
PIM3 (dBc, @2x33dBm)	≤ -120
Impedance (Ω)	50
Return Loss (dB)	≥ 21
Max Input Power (W)	5

**Mechanical and Environmental Specifications**

Dimension (mm)	N F/M: Ø30 x 35 (excluding connector and bracket)
	4.3-10 F/M: Ø30 x 35 (excluding connector and bracket)
	7/16 version: Ø35 x 35 (excluding connector and bracket)
Weight (kgs)	N F/M: 0.22 (including connector and bracket)
	4.3-10 F/M: 0.22 (including connector and bracket)
	7/16 F/M: 0.27 (including connector and bracket)
Ingress Protection	IP55
Operating Temperature (°C)	-55 to +125
Operating RH (%)	≤ 95

**Packing Information**

Packing Size (mm)	70 x 30 x 30
SKU (unit/inner carton)	100 pieces per inner carton/box

(D)28NYY660  
(D)29NYY660  
(D)20NYY660

**E56xxx15-V02**  
**Attenuator 5W**  
**N / 4.3-10 / 7/16**  
**DC-4000**

