

A11x5210-V00
Indoor Omni Directional Antenna
V-Pol 1-port 2/5dBi
698-960 / 1425-6000



Omni Indoor 698-960/1425-6000 2/5dBi

Type	A1115210-v00 (4.3-10 Female)			A1135210-v00 (N Female)	
	Frequency (MHz)	698-806	806-960	1425-2700	3300-4000
Gain (dBi)	1.5	2.0	3.0	4.0	4.5
VSWR	≤ 2.0	≤ 2.0	≤ 1.5	≤ 1.5	≤ 2.0
Polarization	Vertical				
PIM3 (dBc, @2x43dBm)	≤ -150				
Horizontal Beamwidth (°)	360				
Vertical Beamwidth (°)	95	80	38	32	29
Input Impedance (ohm)	50				
Max. Input Power (W)	50				
Lightning Protection	DC Grounded				
Connector	4.3-10 Female			N Female	
Dimension (mm)	Ø204 x 125				
Weight (kgs)	Approx. 0.40				
Reflector Material	Aluminum				
Radome Material	ABS (UV Stabilized)				
Operating Temperature (°C)	-40 to +65				

(A)4WNB41117907YR/3WOB41117907YR



A11x5210-V00
Indoor Omni Directional Antenna
V-Pol 1-port 2/5dBi
698-960 / 1425-6000

