

**A11x5212-V00**  
**Indoor Omni Directional Antenna**  
**V-Pol 1-port 2/5dBi**  
**698-960 / 1425-6000**



**Omni Indoor 698-960/1425-6000 2/5dBi**

Type	A1115212-v00 (4.3-10 Female)			A1135212-v00 (N Female)	
	698-806	806-960	1425-2700	3300-4000	4900-6000
Frequency (MHz)	698-806	806-960	1425-2700	3300-4000	4900-6000
Gain (dBi)	1.5	2.0	3.0	4.0	4.5
VSWR	≤ 2.0	≤ 2.0	≤ 1.5	≤ 1.5	≤ 2.0
Polarization	Vertical				
PIM3 (dBc, @2x43dBm)	≤ -150				
Horizontal Beamwidth (°)	360				
Vertical Beamwidth (°)	95	80	38	32	29
Input Impedance (ohm)	50				
Max. Input Power (W)	50				
Lightning Protection	DC Grounded				
Connector	4.3-10 Female			N Female	
Dimension (mm)	Ø204 x 125				
Weight (kgs)	Approx. 0.40				
Reflector Material	Aluminum				
Radome Material	ABS (UV Stabilized), <b>UL94V0</b>				
Operating Temperature (°C)	-40 to +65				

(A)4WNB41117907YR/3WOB41117907YR



**A11x5212-V00**  
**Indoor Omni Directional Antenna**  
**V-Pol 1-port 2/5dBi**  
**698-960 / 1425-6000**

