

B13x100x-V00
Omni Antenna (Mini)
V-Pol 1-port 3/4dBi
698-960 / 1425-4000



V-Pol Omni 698-960 / 1425-4000 3/4dBi

Preliminary

Type	Cubic Column	B1311008-V00 (4.3-10 Female)		B1331008-V00 (N Female)
	Cylindrical Column	B1311009-V00 (4.3-10 Female)		B1331009-V00 (N Female)
Frequency Range (MHz)		698-960	1425-2700	3300-4000
Gain (dBi)		3	4	4.5
VSWR		≤ 1.8		
3 rd Order PIM (dBc)		≤ -153 @ 2x43dBm		
Polarization		Vertical		
Horizontal Beamwidth (°)		360		
Vertical Beamwidth (°)		80	52	38
Input Impedance (ohm)		50		
Max. Input Power (W)		100		
Lightning Protection		DC Grounded		
Connector Type		1 x 4.3-10 Female	1 x N Female	
Dimension (mm)		66 x 66 x 190	Ø63 x 190	
Weight (kgs)		Cubic Column: 0.35	Cylindrical Column: 1.0	
Radome Material		UV-ABS		
Radiator Material		Aluminum		
Operating Temperature (°C)		-40 to +65		
Mounting		Mounting Clamp for Pole Ø38-Ø52 included		

(A)4WNB51115907KR/4WOB51115907KR
(A)4WN51115907KR/4WO51115907KR

B13x100x-V00
Omni Antenna (Mini)
V-Pol 1-port 3/4dBi
698-960 / 1425-4000



B1311008-V00
B1331008-V00
 Cubic Column

B1311009-V00
B1331009-V00
 Cylindrical Column

