

B3212019-V01
Directional Antenna 698-960/4*1710-2690
XXXXX-Pol 10-port 11/13/13/13/13dBi 65°
Electrical Downtilt (4/2-12T) with Internal RET




XXXXXPol Directional 698-960/4*1710-2690 11/13/13/13/13dBi 65° 4°/2-12°T

Preliminary


Type	B3212019-v01			
Frequency Range (MHz)	698-960	1710-1920	1920-2170	2170-2690
Gain (dBi)	2 x 11±1	8 x 13±1	8 x 13±1	8 x 13±1
VSWR	≤ 1.5			
3 rd Order PIM (dBc)	≤ -150 @ 2x43dBm			
Polarization	±45°			
Electrical Tilt (°)	4 (Fixed)	2-12		
Horizontal Beamwidth (°)	68±7	65±5	60±5	60±5
Vertical Beamwidth (°)	30	20	15	15
Input Impedance (Ω)	50			
Max. Input Power (W)	250			
Front-to-Back Ratio (dB)	≥ 22			
First Sidelobe Suppression (dB)	≤ -14			
Cross-polar Discrimination (dB)	≥ 15 (±60°: ≥ 8)			
Isolation (dB)	≥ 25 (Intra Band) / ≥ 28 (Inter Band)			
Lightning Protection	DC Grounded			
Connector Type	10 x 4.3-10 Female			
Connector Location	Bottom			
Dimension (mm)	1130 x 385 x 137			
Weight (kgs)	18			
Radome Material	UPVC			
Mechanical Tilt (°)	0-15			
Rated Wind Velocity (km/h)	210			
Operating Temperature (°C)	-40 to +60			
Pole Size (mm)	Ø50 to Ø115			
RET	Internal RET (comply with AISG2.0/3GPP)			
Smart Bias Tee	Internal SBT at Y1 +45° Port			

(K)UJFB838142424222QE67UCL

B3212019-V01
Directional Antenna 698-960/4*1710-2690
XXXXX-Pol 10-port 11/13/13/13/13dBi 65°
Electrical Downtilt (4/2-12T) with Internal RET



698-960 ±45°



1710-2690 ±45°

