

B3212020-V01
Directional Antenna 698-960/4*1710-2690
XXXXX-Pol 10-port 13/15/15/15/15dBi 65°
Electrical Downtilt (4-14/2-12T) with Internal RET




XXXXXPol Directional 698-960/4*1710-2690 13/15/15/15/15dBi 65° 4-14°/2-12°T

Preliminary


Type	B3212020-v01			
Frequency Range (MHz)	698-960	1710-1920	1920-2170	2170-2690
Gain (dBi)	2 x 13±1	8 x 15±1	8 x 15±1	8 x 15±1
VSWR	≤ 1.5			
3 rd Order PIM (dBc)	≤ -150 @ 2x43dBm			
Polarization	±45°			
Electrical Tilt (°)	4-14	2-12		
Horizontal Beamwidth (°)	68±7	65±5	60±5	60±5
Vertical Beamwidth (°)	16	12	12	12
Input Impedance (Ω)	50			
Max. Input Power (W)	250			
Front-to-Back Ratio (dB)	≥ 22			
First Sidelobe Suppression (dB)	≤ -15			
Cross-polar Discrimination (dB)	≥ 15 (±60°: ≥ 8)			
Isolation (dB)	≥ 25 (Intra Band) / ≥ 28 (Inter Band)			
Lightning Protection	DC Grounded			
Connector Type	10 x 4.3-10 Female			
Connector Location	Bottom			
Dimension (mm)	1580 x 385 x 137			
Weight (kgs)	27			
Radome Material	UPVC			
Mechanical Tilt (°)	0-20			
Rated Wind Velocity (km/h)	210			
Operating Temperature (°C)	-40 to +60			
Pole Size (mm)	Ø50 to Ø115			
RET	Internal RET (comply with AISG2.0/3GPP)			
RET Connector Type	8-pin RS485 female x 1, 8-pin RS485 male x 1			

(K)

B3212020-V01
Directional Antenna 698-960/4*1710-2690
XXXXX-Pol 10-port 13/15/15/15/15dBi 65°
Electrical Downtilt (4-14/2-12T) with Internal RET



698-960 $\pm 45^\circ$



1710-2690 $\pm 45^\circ$

