

E23xxx64-V02
Attenuator 200W
N / 4.3-10 / 7/16
698-4000



Attenuator 698-4000 200W

Type	N F/M	E2330364-v02	E2330564-v02	E2330664-v02	E2331064-v02
	4.3-10 F/M	E2310364-v02	E2310564-v02	E2310664-v02	E2311064-v02
	7/16 F/M	E2350364-v02	E2350564-v02	E2350664-v02	E2351064-v02
Attenuation (dB)		3	5	6	10
Attenuation Tolerance (dB)		±0.7	±1.0	±1.0	±1.0

Type	N F/M	E2331564-v02	E2332064-v02	E2333064-v02	E2334064-v02
	4.3-10 F/M	E2311564-v02	E2312064-v02	E2313064-v02	E2314064-v02
	7/16 F/M	E2351564-v02	E2352064-v02	E2353064-v02	E2354064-v02
Attenuation (dB)		15	20	30	40
Attenuation Tolerance (dB)		±1.0	±1.3	±1.3	±1.5

Electrical Specifications

Frequency (MHz)	698 - 4000
PIM3 (dBc, @2x43dBm)	≤ -150
Impedance (Ω)	50
Return Loss (dB)	≥ 19
Max Input Power (W)	200

Mechanical and Environmental Specifications

Dimension (mm)	250 x 176 x 97.5 (excluding connector and bracket)
Weight (kgs)	N F/M: 7.5 (including connector and bracket)
	4.3-10 F/M: 7.7 (including connector and bracket)
	7/16 F/M: 7.9 (including connector and bracket)
Ingress Protection	IP65
Operating Temperature (°C)	-40 to +65
Operating RH (%)	≤ 95
Mounting	Wall Mount or Pole Mount

Packing Information

Packing Size (mm)	415 x 365 x 285
SKU (unit/inner carton)	4 pieces per inner carton/box

(D)4351B660/4351C660/4351D660/4351G660/4351H660/4351M660/4351K660/4351L660
(D)4451B660/4451C660/4451D660/4451G660/4451H660/4451M660/4451K660/4451L660
(D)4551B660/4551C660/4551D660/4551G660/4551H660/4551M660/4551K660/4551L660

E23xxx64-V02
Attenuator 200W
N / 4.3-10 / 7/16
698-4000

