

H1xx10x4-V02
Hybrid Combiner 2-in/2-out
PIM -150dBc / -155dBc / -160dBc
698-2700



2x2 Hybrid Combiner 698-2700

Preliminary

Type	PIM ≤ -150dBc	H1331014.v02	H1311024.v02	H1351034.v02
	PIM ≤ -155dBc	H1231014.v02	H1211024.v02	H1251034.v02
	PIM ≤ -160dBc	H1131014.v02	H1111024.v02	H1151034.v02
Frequency (MHz)	698-2700			
Insertion Loss (dB)	3 ±0.5			
VSWR	≤ 1.25			
Isolation (dB)	≥ 28			
PIM3 (dBc, @2x43dBm)	See above type number table			
Input Impedance (ohm)	50			
Max. Input Power (W)	300	500	700	
Connector	N Female	4.3-10 Female	7/16 Female	
Weight (kgs) (including mounting bracket and connectors)	0.40	0.50	0.70	
Dimension (mm)	161 x 42 x 40 (excluding mounting bracket and connectors)			
Ingress Protection Class	IP65 (for outdoor and indoor)			
Operating RH (%)	≤ 95			
Operating Temperature (°C)	-40 to +65			
Mounting	Wall Mount			
Colour	Light Grey			

(D)40233460/42333460/44333460
(D)60233460/62333460/64333460
(D)80233460/82333460/84333460

