

H3xx10x4-V02
Hybrid Combiner 2-in/2-out
PIM -150dBc / -155dBc / -160dBc
698-3800



2x2 Hybrid Combiner 698-3800

Preliminary

Type	PIM ≤ -150dBc	H3331014-V02 (KB010624)	H3311024-V02 (KB610624)	H3351034-V02 (KB110624)
	PIM ≤ -155dBc	H3231014-V02 (KB020624)	H3211024-V02 (KB620624)	H3251034-V02 (KB120624)
	PIM ≤ -160dBc	H3131014-V02 (KB030624)	H3111024-V02 (KB630624)	H3151034-V02 (KB130624)
Frequency (MHz)	698-3800			
Insertion Loss (dB)	3 ±0.5			
VSWR	≤ 1.2			
Isolation (dB)	≥ 25			
PIM3 (dBc, @2x43dBm)	See above type number table			
Input Impedance (ohm)	50			
Max. Input Power (W)	300	500	700	
Connector	N Female	4.3-10 Female	7/16 Female	
Weight (kgs) (including mounting bracket and connectors)	0.48	0.50	0.70	
Dimension (mm)	158.9 x 42 x 29.5 (excluding mounting bracket and connectors)			
Ingress Protection Class	IP65 (for outdoor and indoor)			
Operating RH (%)	≤ 95			
Operating Temperature (°C)	-40 to +65			
Mounting	Wall Mount			
Colour	Light Grey			

(D)47333460/49333460/414333460
(D)67333460/69333460/614333460
(D)87333460/89333460/814333460

