

L5xx0254-V03

Termination Load 50 ohm

PIM: -160/-155/-150dBc 25W

DC-4000 N / 4.3-10 / 7/16: Male / Female



Termination Load 50ohm DC-4000 25W

Type	PIM ≤ -160dBc @2x43dBm	L5130254-v03 (N-Female)	L5140254-v03 (N-Male)
	PIM ≤ -155dBc @2x43dBm	L5230254-v03 (N-Female)	L5240254-v03 (N-Male)
	PIM ≤ -150dBc @2x43dBm	L5330254-v03 (N-Female)	L5340254-v03 (N-Male)
	PIM ≤ -160dBc @2x43dBm	L5110254-v03 (4.3-10-Female)	L5120254-v03 (4.3-10-Male)
	PIM ≤ -155dBc @2x43dBm	L5210254-v03 (4.3-10-Female)	L5220254-v03 (4.3-10-Male)
	PIM ≤ -150dBc @2x43dBm	L5310254-v03 (4.3-10-Female)	L5320254-v03 (4.3-10-Male)
	PIM ≤ -160dBc @2x43dBm	L5150254-v03 (7/16-Female)	L5160254-v03 (7/16-Male)
	PIM ≤ -155dBc @2x43dBm	L5250254-v03 (7/16-Female)	L5260254-v03 (7/16-Male)
	PIM ≤ -150dBc @2x43dBm	L5350254-v03 (7/16-Female)	L5360254-v03 (7/16-Male)
Power Rating (W)	25		
Frequency (MHz)	DC - 4000		
PIM3 (dBc)	See Above Type Number Selection Table		
Impedance (Ω)	50		
VSWR	≤ 1.25		
Dimension (mm) (excluding connector)	Ø63 x 140		
Ingress Protection	IP65		
Operating Temperature (°C)	-40 to +80		

(C)YYY63YOPH94MEOW
(C)YYY63YQPH94MEOW
(C)YYY63YEPH94MEOW

L5xx0254-V03
Termination Load 50 ohm
PIM: -160/-155/-150dBc 25W
DC-4000 N / 4.3-10 / 7/16: Male / Female

