

L5xx1004-V03

Termination Load 50 ohm

PIM: -160/-155/-150dBc 100W

DC-4000 N / 4.3-10 / 7/16: -Male / Female



Termination Load 50ohm DC-4000 100W

Type	PIM= -160dBc @2x43dBm	L5131004-v03 (N-Female)	L5141004-v03 (N-Male)
	PIM= -155dBc @2x43dBm	L5231004-v03 (N-Female)	L5241004-v03 (N-Male)
	PIM= -150dBc @2x43dBm	L5331004-v03 (N-Female)	L5341004-v03 (N-Male)
	PIM= -160dBc @2x43dBm	L5111004-v03 (4.3-10-Female)	L5121004-v03 (4.3-10-Male)
	PIM= -155dBc @2x43dBm	L5211004-v03 (4.3-10-Female)	L5221004-v03 (4.3-10-Male)
	PIM= -150dBc @2x43dBm	L5311004-v03 (4.3-10-Female)	L5321004-v03 (4.3-10-Male)
	PIM= -160dBc @2x43dBm	L5151004-v03 (7/16-Female)	L5161004-v03 (7/16-Male)
	PIM= -155dBc @2x43dBm	L5251004-v03 (7/16-Female)	L5261004-v03 (7/16-Male)
	PIM= -150dBc @2x43dBm	L5351004-v03 (7/16-Female)	L5361004-v03 (7/16-Male)
Power Rating (W)	100		
Frequency (MHz)	DC - 4000		
PIM3 (dBc)	See Above Type Number Selection Table		
Impedance (Ω)	50		
VSWR	≤ 1.20		
Dimension (mm) (excluding connector)	180 x 150 x 62		
Weight (kgs) (including connector)	Female: 2.545 approx.		
	Male: 2.530 approx.		
Ingress Protection	IP65		

L5xx1004-V03
Termination Load 50 ohm
PIM: -160/-155/-150dBc 100W
DC-4000 N / 4.3-10 / 7/16: -Male / Female

