

S0X3X014-V02
Power Splitter 2- / 3- / 4-way 300W N
PIM -150dBc / -140dBc
380-2700



Power Splitter 300W 380-2700				<i>Preliminary</i>
Type	PIM: -150dBc	S0332014-v02 KS010002	S0333014-v02 KS010003	S0334014-v02 KS010004
	PIM: -140dBc	S0432014-v02 KS012302	S0433014-v02 KS012303	S0434014-v02 KS012304
Frequency (MHz)	380-2700			
Splitting Output	2-way	3-way	4-way	
Distribution Loss (dB)	3.0	4.8	6.0	
In-band Ripple (dB)	≤0.3	≤0.5	≤0.8	
Return Loss (dB)	≥19			
PIM3 (dBc, @2x43dBm)	See Above Type Number			
Input Impedance (ohm)	50			
Max. Input Power (W)	300			
Connector	N Female			
Colour	Light Grey			
Mounting	Wall Mount			
Weight (kgs) (including mounting bracket and connectors)	Approx. 0.5	Approx. 0.57	Approx. 0.63	
Dimension (mm) (including mounting bracket and connectors)	272 x 61 x 42	325 x 61 x 42	360 x 61 x 60	
Ingress Protection Class	IP65 (for outdoor and indoor)			

(D) N21631O8341QTNY/ N21641O8341QTNY/ N21651O8341QTNY/
(D) M21631O8341QTNY/ M21641O8341QTNY/ M21651O8341QTNY/