

S1x3x014-V02
Power Splitter 2- / 3- / 4-way 300W
PIM -150/-155/-160dBc N Female
698-2700



Power Splitter 300W 698-2700 (Square Tube, Screwed-in)

Type	PIM \leq -150dBc @2x43dBm	S1332014-V02	S1333014-V02	S1334014-V02
	PIM \leq -155dBc @2x43dBm	S1232014-V02	S1233014-V02	S1234014-V02
	PIM \leq -160dBc @2x43dBm	S1132014-V02	S1133014-V02	S1134014-V02
Frequency (MHz)	698-2700			
Splitting Output	2-way	3-way	4-way	
Distribution Loss (dB)	3.0	4.8	6.0	
Insertion Loss (dB)	\leq 0.2	\leq 0.4	\leq 0.5	
Return Loss (dB)	\geq 21			
PIM3 (dBc, @2x43dBm)	See Above Type Number List			
Input Impedance (ohm)	50			
Max. Input Power (W)	300			
Connector	N Female			
Weight (kgs) (including mounting bracket and connectors)	Approx. 0.34	Approx. 0.38	Approx. 0.56	
Dimension (mm) (excluding mounting bracket and connectors)	199.1 x 25 x 25	235.2 x 25 x 25	235.2 x 25 x 25	
Ingress Protection Class	IP65 (for outdoor and indoor)			
Operating Temperature (°C)	-25 to +65			
Operating RH (%)	\leq 95			
Mounting	Wall Mount			

(D)40313160/40314160/40315160
(D)60313160/60314160/60315160
(D)80313160/80314160/80315160

