

S1x3x114-V02
Power Splitter 2- / 3- / 4-way 300W
PIM -150/-155/-160dBc N Female
698-2700



Power Splitter 300W 698-2700 (Round Tube, Screwed-in)

Type	PIM \leq -150dBc @2x43dBm	S1332114-v02	S1333114-v02	S1334114-v02
	PIM \leq -155dBc @2x43dBm	S1232114-v02	S1233114-v02	S1234114-v02
	PIM \leq -160dBc @2x43dBm	S1132114-v02	S1133114-v02	S1134114-v02
Frequency (MHz)	698-2700			
Splitting Output	2-way	3-way	4-way	
Distribution Loss (dB)	3.0	4.8	6.0	
Insertion Loss (dB)	\leq 0.3	\leq 0.4	\leq 0.5	
Return Loss (dB)	\geq 19			
PIM3 (dBc, @2x43dBm)	See Above Type Number List			
Input Impedance (ohm)	50			
Max. Input Power (W)	300			
Connector	N Female			
Weight (kgs) (including mounting bracket and connectors)	Approx. 0.18	Approx. 0.23	Approx. 0.28	
Dimension (mm) (excluding mounting bracket and connectors)	199.1 x 25 x 25	235.2 x 25 x 25	235.2 x 25 x 25	
Ingress Protection Class	IP65 (for outdoor and indoor)			
Operating Temperature (°C)	-25 to +65			
Operating RH (%)	\leq 95			
Mounting	Wall Mount			

(D)45413160/45414160/45415160
(D)65413160/65414160/65415160
(D)85413160/85414160/85415160

