

S1x5x034-V02
Power Splitter 2- / 3- / 4-way 700W
PIM -150/-155/-160dBc 7/16 Female
698-2700



Power Splitter 700W 698-2700 (Square Tube, Screwed-in)

Type	PIM \leq -150dBc @2x43dBm	S1352034-V02	S1353034-V02	S1354034-V02
	PIM \leq -155dBc @2x43dBm	S1252034-V02	S1253034-V02	S1254034-V02
	PIM \leq -160dBc @2x43dBm	S1152034-V02	S1153034-V02	S1154034-V02
Frequency (MHz)	698-2700			
Splitting Output	2-way	3-way	4-way	
Distribution Loss (dB)	3.0	4.8	6.0	
Insertion Loss (dB)	\leq 0.3	\leq 0.4	\leq 0.5	
Return Loss (dB)	\geq 19			
PIM3 (dBc, @2x43dBm)	See Above Type Number List			
Input Impedance (ohm)	50			
Max. Input Power (W)	700			
Connector	7/16 Female			
Weight (kgs) (including mounting bracket and connectors)	Approx. 0.47	Approx. 0.58	Approx. 0.62	
Dimension (mm) (excluding mounting bracket and connectors)	206.6 x 25 x 25	235.2 x 25 x 25	235.2 x 25 x 25	
Ingress Protection Class	IP65 (for outdoor and indoor)			
Operating Temperature (°C)	-25 to +65			
Operating RH (%)	\leq 95			
Mounting	Wall Mount			

(D)44413160/44414160/44415160
(D)64413160/64414160/64415160
(D)84413160/84414160/84415160

