

**S3x1x024-V03**  
**Power Splitter 2- / 3- / 4-way 4.3-10 500W**  
**PIM -160dBc / -155dBc / -150dBc / -140dBc**  
**698-4000**



Power Splitter 500W 698-4000 (Square Tube)				<i>Preliminary</i>
Type	PIM $\leq$ -160dBc	<b>S3112024-V03</b>	<b>S3113024-V03</b>	<b>S3114024-V03</b>
	PIM $\leq$ -155dBc	<b>S3212024-V03</b>	<b>S3213024-V03</b>	<b>S3214024-V03</b>
	PIM $\leq$ -150dBc	<b>S3312024-V03</b>	<b>S3313024-V03</b>	<b>S3314024-V03</b>
	PIM $\leq$ -140dBc	<b>S3412024-V03</b>	<b>S3413024-V03</b>	<b>S3414024-V03</b>
Frequency (MHz)	698-4000			
Splitting Output	2-way	3-way	4-way	
Distribution Loss (dB)	$\leq$ 3.5	$\leq$ 5.4	$\leq$ 6.9	
VSWR	$\leq$ 1.3			
PIM3 (dBc, @2x43dBm)	See Above Type Number Table			
Input Impedance (ohm)	50			
Max. Input Power (W)	500			
Max. Peak Power (W)	1,500			
Connector	4.3-10 Female (Screwed-in)			
Dimension (mm) (excluding mounting bracket and connectors)	216 x 25 x 25	216 x 25 x 25	243 x 25 x 25	
Ingress Protection Class	IP65 (for outdoor and indoor)			
Operating Temperature (°C)	-40 to +80			
Mounting	Built-in Bracket for wall mount			
Colour	Light Grey			

(C)T3QP1581TQOW/T4QP1581TQOW/T5QP1581TQOW

