

S3x3x014-V03
Power Splitter 2- / 3- / 4-way N 300W
PIM -160dBc / -155dBc / -150dBc / -140dBc
698-4000



Power Splitter 300W 698-4000 (Square Tube)				<i>Preliminary</i>
Type	PIM \leq -160dBc	S3132014-V03	S3133014-V03	S3134014-V03
	PIM \leq -155dBc	S3232014-V03	S3233014-V03	S3234014-V03
	PIM \leq -150dBc	S3332014-V03	S3333014-V03	S3334014-V03
	PIM \leq -140dBc	S3432014-V03	S3433014-V03	S3434014-V03
Frequency (MHz)	698-4000			
Splitting Output	2-way	3-way	4-way	
Distribution Loss (dB)	\leq 3.5	\leq 5.4	\leq 6.9	
VSWR	\leq 1.3			
PIM3 (dBc, @2x43dBm)	See Above Type Number Table			
Input Impedance (ohm)	50			
Max. Input Power (W)	300			
Max. Peak Power (W)	1,200			
Connector	N Female (Screwed-in)			
Dimension (mm) (excluding mounting bracket and connectors)	216 x 25 x 25	216 x 25 x 25	243 x 25 x 25	
Ingress Protection Class	IP65 (for outdoor and indoor)			
Operating Temperature (°C)	-40 to +80			
Mounting	Built-in Bracket for wall mount			
Colour	Light Grey			

(C)T3OP1581TQOW/T4OP1581TQOW/T5OP1581TQOW

