

S3x5x034-V03
Power Splitter 2- / 3- / 4-way 7/16 700W
PIM -160dBc / -155dBc / -150dBc / -140dBc
698-4000



Power Splitter 700W 698-4000 (Square Tube)				<i>Preliminary</i>
Type	PIM \leq -160dBc	S3152034-V03	S3153034-V03	S3154034-V03
	PIM \leq -155dBc	S3252034-V03	S3253034-V03	S3254034-V03
	PIM \leq -150dBc	S3352034-V03	S3353034-V03	S3354034-V03
	PIM \leq -140dBc	S3452034-V03	S3453034-V03	S3454034-V03
Frequency (MHz)	698-4000			
Splitting Output	2-way	3-way	4-way	
Distribution Loss (dB)	\leq 3.5	\leq 5.4	\leq 6.9	
VSWR	\leq 1.3			
PIM3 (dBc, @2x43dBm)	See Above Type Number Table			
Input Impedance (ohm)	50			
Max. Input Power (W)	700			
Max. Peak Power (W)	2,000			
Connector	7/16 Female (Screwed-in)			
Dimension (mm) (excluding mounting bracket and connectors)	216 x 25 x 25	216 x 25 x 25	243 x 25 x 25	
Ingress Protection Class	IP65 (for outdoor and indoor)			
Operating Temperature (°C)	-40 to +80			
Mounting	Built-in Bracket for wall mount			
Colour	Light Grey			

(C)T3EP1581TQOW/T4EP1581TQOW/T5EP1581TQOW

