

**S3x5x134-V02**  
**Power Splitter 2- / 3- / 4-way DIN 700W**  
**PIM -150dBc / -155dBc / -160dBc**  
**698-4000**



Power Splitter 700W 698-4000 (Round Tube)

*Preliminary*

Type	<b>S3352134-v02</b> PIM ≤ -150dBc		<b>S3353134-v02</b> PIM ≤ -150dBc		<b>S3354134-v02</b> PIM ≤ -150dBc	
	<b>S3252134-v02</b> PIM ≤ -155dBc		<b>S3253134-v02</b> PIM ≤ -155dBc		<b>S3254134-v02</b> PIM ≤ -155dBc	
	<b>S3152134-v02</b> PIM ≤ -160dBc		<b>S3153134-v02</b> PIM ≤ -160dBc		<b>S3154134-v02</b> PIM ≤ -160dBc	
Frequency (MHz)	698-4000					
Splitting Output	2-way		3-way		4-way	
Distribution Loss (dB)	3.0		4.8		6.0	
Insertion Loss (dB)	< 0.25		< 0.35		< 0.4	
Return Loss (dB)	≥ 19					
PIM3 (dBc, @2x43dBm)	See above type number table					
Input Impedance (ohm)	50					
Max. Input Power (W)	700					
Connector	7/16 Female (Screwed-in)					
Weight (kgs) (including mounting bracket and connectors)	0.58		0.64		0.71	
Dimension (mm) (excluding mounting bracket and connectors)	223.7 x 25 x 25		258 x 25 x 25		258 x 25 x 25	
Ingress Protection Class	IP65 (for outdoor and indoor)					
Operating RH (%)	≤ 95					
Operating Temperature (°C)	-25 to +65					
Mounting	Built-in Bracket for wall mount					
Colour	Light Grey					

(D)48223160/48224160/48225160  
(D)68223160/68224160/68225160  
(D)88223160/88224160/88225160

