

S8x5x024-V02
Power Splitter 2- / 3- / 4-way 500W
PIM -150/-155/-160dBc 7/16 Female
340-3800



Power Splitter 500W 340-3800 (Square Tube, Screwed-in)

Type	PIM \leq -150dBc @2x43dBm	S8352024-V02	S8353024-V02	S8354024-V02
	PIM \leq -155dBc @2x43dBm	S8252024-V02	S8253024-V02	S8254024-V02
	PIM \leq -160dBc @2x43dBm	S8152024-V02	S8153024-V02	S8154024-V02
Frequency (MHz)	340-3800			
Splitting Output	2-way	3-way	4-way	
Distribution Loss (dB)	3.0	4.8	6.0	
Insertion Loss (dB)	\leq 0.3	\leq 0.6	\leq 0.6	
Return Loss (dB)	\geq 19 (340-2700) / \geq 18 (3400-3800)			
PIM3 (dBc, @2x43dBm)	See Above Type Number List			
Input Impedance (ohm)	50			
Max. Input Power (W)	500			
Peak Power (W)	2000			
Connector	7/16 Female			
Weight (kgs) (including mounting bracket and connectors)	Approx. 0.57	Approx. 0.63	Approx. 0.76	
Dimension (mm) (excluding mounting bracket and connectors)	249 x 25 x 25	272.5 x 25 x 25	294.9 x 25 x 25	
Ingress Protection Class	IP65 (for outdoor and indoor)			
Operating Temperature ($^{\circ}$ C)	-40 to +65			
Operating RH (%)	\leq 95			
Mounting	Wall Mount			

(D)4621Y160
(D)6621Y160
(D)8621Y160

